

Slim Rugged - Intel 7th Gen Mobile - IP51

A tiny foot print, ideal for the most restricted spaces where only the smallest will do!

Our smallest range of computers! The Slim Rugged was designed to sit flush on a wall behind a screen: it was developed for digital signage applications, where space was the main constraint. The heat pipe cooling solution made it possible to reach optimal passive cooling without compromising performance in this very small footprint.



Key Features

- Processor: Celeron - i5
- Operating Range: -10C to 30C
- Dual Display
- 1Gbe LAN
- Maintenance free

Key benefits of FANLESS and RUGGED computers



No fans obviously means no noise, but it's not the only benefit!



No fans allow an important decrease in power consumption, making our products more sustainable!



A fanless computer eliminates the risk to draw in dust and dirt from the environment, the cause of potential failures and costly downtime.



The absence of moving parts enable our products to resist shocks and vibrations, for an increased reliability.



They are built to withstand harsh and constrained working conditions.



High Ingress Protection (IP) rating, indication the protection level of products against both solid and liquids in electrical enclosures



The in-house designed and milled aluminium chassis is optimized for efficient passive cooling and durability. Its conception proved their reliability in extended operating temperatures



The aluminium used for the chassis production is repurposed and recycled, and the production waste is recycled too!

Slim Rugged - Intel 7th Gen Mobile - IP51



Rear view

Technical Specification

Processor	Intel Celeron 3865U - 2 Cores / 2 Threads - 1.80 GHz - 2MB Cache Intel i3 7020U - 2 Cores / 4 Threads - 2.30 GHz - 3MB Cache Intel i5 7200U - 2 Cores / 4 Threads - 2.50 GHz - 3MB Cache		
Memory	Slots: 2x SO-DIMM Slots MAX Capacity: 32GB Type: DDR4-2133 1.2V SO-DIMM ECC Support: No	Storage	256GB M.2 SSD 2260 /
Graphics Controller	Intel HD Graphics 610 or 620 (depending on CPU)	Graphics Interface	1 x MiniDisplay - 4096 x 2160 @ 60HZ 1 x HDMI - 4096 x 2160 @ 30HZ
Network Interface	i211-AT - 1 x RJ45 - 10/100/1000 Mbps	Network Options	RTL8188EE - Wi-Fi IEEE 802.11 b/g/n - 2.4GHz/5Ghz
Network Feature	PXE	Remote Management	
Hardware Monitoring	Hardware Watch Dog	Supported OS	Windows 7 - 32/64 bit Windows 10 - 32/64 bit Linux
Encryption			
Power Input	2.5 x 5.5mm DC Jack		
Input Voltage	12V		
Consumption	22-35w		

Physical Specification

I/O Front	Power Switch, 1x USB 3.0, 1x USB 3.0 Type C,	LED Front	Power
I/O Rear	DC-In 12V, 1x RJ45 for LAN, 2x USB3.0, 1x HDMI, 1x MDP	LED Rear	Network Uplink/Activity
I/O Optional	Dual Wireless Antenna	COM Port Option	
Operational Temp	-10C to 30C (14F to 86F)	Storage Temp	-20°C to 70°C (-4°F to 158°F)
Maximum relative humidity	5% to 95%	Cooling Type	Passive Cooling
Size	30 x 200 x 112mm	Weight	1.02KG
Accessories	Power supply, power cord	Optional Accessories	Wireless Antenna
Certifications	CE	Warranty	3 Years